

Plaster Coarse Finish

DESCRIPTION:

A ready to use, cementations decorative colored render. It consist of a mortar made up selected sand, Portland cement, pigments, chemicals additives to increase impermeability and strength, light weight aggregate and others. **Aman Coarse Finish** produces wide range of colors for further customer satisfaction.

ADVANTAGES:

- **Aman Coarse Finish** is a pre-bagged high quality render coat, fast and easy to use, it requires only addition of water on the site prior to use.
- It is practically crack free due to the cellulose fiber added to the material.
- Its water and weather resistant, it is suitable to using in hot and humid weather as well as cold weather.
- It can used as finished plastering directly on block, bricks, concrete surface or finished plastering, with high bond strength on the substrate.
- It can be offer with a variety of colors to satisfy all tastes of clients.
- Its economical comparing to other traditional ways of finishing, like marble or stone cladding, as well as more durable comparing to difference kind of paints.

SHELF LIFE:

Under normal conditions and when kept dry, the shelf life of **Aman Coarse Finish** is 12 months from the manufacturing date, inventory should be rotated.

PACKAGING:

Aman Coarse Finish is available in 25 kg/bag

COVERAGE:

Approximately 1.6 kg/m² of dry product per each mm of coat thickness.

APPLICATION:

- The surface should be clean and free from dust, paint and all lose particles. Dampen the surface before application.
- Mix the material with the same quantity of water for each mix to avoid shading. 4-5 ltr can used.
- Apply the mix directly on a dampened substrate on average thickness of 10mm by trowel.
- Carefully level and smooth the render. When the mortar starts to harden, it scraped uniformly on the entire surface using special trowel to give desire finish.
- Do not apply the material if rain predicted.

TECHNICAL PROPERTIES:

Type of blinder	Portland Cement
Filler	Graded crushed limestone grain of 2 mm. max.
Dry Density	1.5 + 0.1 kg./Ltr.
Wet Density	About 1.2 + 0.1 kg/Ltr.
Compressive Strength	6.8 N/mm ²
Flexural Strength	3.6 N/mm ²
Bonding Strength	0.72 N/mm ²

Coarse finish plaster is manufactured to comply with SASO-EN-998-1 specifications.

GUARANTEE:

The information given in based of knowledge and performance of the material. Every precaution took in the manufacturing of the product and the responsibility is limited to the quality of supplies, with no guarantee of results in the field, as **AMANCRETE** has no control over site conditions or execution of work.